

**FRAMELESS GLASS TOP**

Model No.	External (mm) W*D*H	Capacity (L)	Operating Temp. (°C)	Rated(V) Current(A)	No. of Shelves	Weight NW./GW.	Shipping dimension
SG250BF	900x660x1200	350	2~6	220V/3.8A	2+bottom	168/207	1000*720*1280
SG350BF	1200x660x1200	460	2~6	220V/4.2A	2+bottom	200/245	1300*720*1280
SG450BF	1500x660x1200	600	2~6	220V/5.5A	2+bottom	220/270	1600*720*1280
SG550BF	1800x660x1200	710	2~6	220V/5.8A	2+bottom	270/320	1900*720*1280

**FEATURES:****REFRIGERATION SYSTEM**

- Operating temperature: 2~6°C, under room temperature of 32°C.
- Environment friendly refrigerant R134a or R404a.
- Fan forced evaporator cooling, and defrost is automatic off cycle.
- Self-contained refrigeration system in the bottom.
- Automatic evaporation of the defrost water by using the high pressure hot gas of the copper pipe.

**CONSTRUCTION**

- Stainless steel base with black paint on the glass as standard, frameless glass top.
- High quality international brand compressor: Embraco aspera or Secop compressor.
- The front glass is heated, side/top/back glasses are double layers, to avoid the condensation.
- Sliding doors at the back, with door mullion heaters.
- All units come with LED light tube as standard.
- Castor feet, digital display controller.

**OPTION**

- Material: Stainless steel #430 and #304 are available.
- Marble base/SS base, or white paint on glass are available.

**Power supply:**

- 220V/50HZ, 60HZ; 110V/60HZ.