



CRA-090-N-DW



CRA-137-N-DW



CRA-183-N-DW

| Model No. | External (mm) W*D*H | Capacity | Operating Temp. (°C) | Rated(V) Current(A) | No. of drawers | Weight NW./GW. | Shipping dimension mm |
|--------------|------------------------|----------------------|-------------------------|------------------------|-------------------|-------------------|--------------------------|
| CRA-090-N-DW | 905x760x850 | 2x1/1*150 GN pans | 2~6 | 220V/2.5 | 2 | 95/99 kgs | 960*820*880 |
| CRA-137-N-DW | 1370x760x850 | 4x1/1*150 GN pans | 2~6 | 220V/3.1 | 4 | 170/174 kgs | 1420*820*880 |
| CRA-183-N-DW | 1835x760x850 | 6x1/1*150 GN pans | 2~6 | 220V/3.1 | 6 | 270/275 kgs | 1890*820*880 |

FEATURES:

REFRIGERATION SYSTEM

- Operating temperature: 2~6℃, under room temperature of 32℃.
- Fan forced evaporator cooling.
- Self-contained refrigeration system in the right side.
- Automatic evaporation of the defrost water by using the high pressure hot gas of the copper pipe.

CONSTRUCTION

- Designed to accommodate GN 1/1 pans (150mm deep).
- 50mm all round insulation with high density PU (40kg/m³).
- High quality international brand compressor: Embraco aspera compressor.
- Waterproof control panel easy to read and control.
- The compressor section can be pulled out for easy cleaning and maintenance.

OPTION

- Stainless steel splash-back to prevent spillage behind the counter.
- Standard stainless steel bullet feet, adjustable from 135 to 165mm, castors with 130mm height is optional.
- Door locks.